


# GOT-2571S

## 5.7" QVGA STN Fanless Touch Panel Computer



- |                     |                    |
|---------------------|--------------------|
| 1. COM1 (RS-232)    | 5. Fuse            |
| COM2 (RS-232)       | 6. Power Connector |
| 2. COM1 (RS-485)    | 7. Sound port      |
| COM3 (RS-232 / 485) |                    |
| 3. USB Host         |                    |
| 4. Ethernet (RJ-45) |                    |



### Features

- ▶ Fanless and low power consumption CPU ARM9
- ▶ 5.7" QVGA color STN LCD
- ▶ Windows® CE.NET supported and flash ROM on-board
- ▶ Slim and compact size design
- ▶ Fanless cooling system and CompactFlash™ card supported
- ▶ NEMA 4 / IP65 compliant front panel
- ▶ Built-in 4-wire resistant touchscreen
- ▶ Over-voltage power protection - fuse

### Introduction

The GOT-2571S series features a fanless and compact-size touch panel design. It is equipped with a 5.7" STN LCD display, Windows® CE.NET, and a low power consumption CPU, the ARM9. The GOT-2571S is a cost-effective choice for operator interface applications, and incorporates a reliable and stable design.

With a fanless CPU and a CompactFlash™ card, the GOT-2571S is especially suitable for vibration-heavy environments, and is used in transportation and semiconductor fields. In addition, the GOT-2571S is also bundled with Windows® CE.NET, which forms a bridge that lets the GOT-2571S be an open HMI solution for system integration. For connecting other devices, the GOT-2571S also provides several interfaces: RS-232/422/485, Ethernet.

### Specifications

Construction	Plastic molding housing
Display	5.7" QVGA Color STN LCD
CPU and Core Logic	ARM9 200MHz
DRAM	64MB system memory on board
Storage	32MB flash memory on board; CompactFlash™ memory card
I/O	2 serial ports (COM1: RS-232/485, COM2: RS-232, COM3: RS-232/485) RS-232 for Active Sync 2 USB 2.0 host 1 Ethernet port (10/100Base-T); 1 Line out

Sound Output	16 bit sound output
Power Input	24V <sub>DC</sub> , 300mA maximum
Dimensions	8.03" (204mm)(W) x 1.9" (48mm)(D) x 5.9" (150mm)(H)
Weight	1.0kg (2.2 lb)
Touchscreen	Type: 4-wire, analog resistive Resolution: continuous Light transmission: above 80% Life: 1 million activation minimum
OS	Windows® CE.NET w/ Compact Framework
Environmental	Operating temperature: 0°C ~ 40°C (32°F ~ 104°F) Relative humidity: 10% ~ 90% @ 40°C, non-condensing Operation vibration: 2.0G, 5~500Hz, random

## LCD

Display Type	STN color LCD
Display Size	5.7" (diagonal)
Max Colors	256
Resolution	320 x 240
Pixel Pitch	0.36 x 0.36 (H x V, mm)
Viewing Angle	(H) 100°, (V) 70°
Luminance	150 cd/m <sup>2</sup>
Storage Temperature	-20~60°C
Operating Temperature	0~40°C
Backlight	CCFL x 1
Contrast Ratio	30:1




## Ordering Information


GOT-2571S	5.7" STN LCD display fanless touch panel computer with 32MB flash memory/ 64MB DRAM onboard and Windows® CE.NET English OS
PS-DC24-50	110~230V <sub>AC</sub> to 24V <sub>DC</sub> , 2.3A, 50W power supply
59125T11800E	ActiveSync cable: COM port cable for GOT-2571S




## Dimensions




Rear View



Front View



Side View



Bottom View